SECTION 1: PRODUCT IDENTIFICATION

Product Name:	Colour Tint SB – All Colors
Synonyms:	
Product Number:	37-CTSB
Company:	Durável
Address:	225 Olympic St., Charlotte NC 28273
Business Phone:	(704) 837-7991
Emergency Phone:	Chemtrec US (800) 424-9300 CNN 1014580
Date of Current Revision:	February 1, 2026

SECTION 2: HAZARD IDENTIFICATION

Classification

OSHA Regulatory Status
This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable Liquids, H226	Category 3
Acute Toxicity, Oral, H303	Category 5
Aspiration Hazard, H304	Category 1
Acute Toxicity, Dermal, H312	Category 4
Skin Corrosion/Irritation, H315	Category 2
Serious Eye Damage/Eye Irritation, H319	Category 2A
Acute Toxicity, Inhalation, H332	Category 4
Specific Target Organ Toxicity, Single Exposure; Respiratory Tract Irritation, H335	Category 3
Germ Cell Mutagenicity, H340	Category 1B
Carcinogenicity, H351	Category 2
Specific Target Organ Toxicity, Repeated Exposure H373	Category 2
Hazardous to the Aquatic Environment, Acute Hazard, H401	Category 2
Hazardous to the Aquatic Environment, Long-Term Hazard, H413	Category 3

EMERGENCY OVERVIEW: This product is an opaque liquid.

DANGER

H226: Flammable Liquid and Vapor.
H303: May be Harmful if Swallowed.
H304: May be Fatal if Swallowed and Enters Airways.
H312: Harmful in Contact with Skin.
H315: Causes Skin Irritation.
H319: Causes Serious Eye Irritation.

H332: Harmful if Inhaled.
H335: May Cause Respiratory Irritation.
H340: May Cause Genetic Defects.
H351: Suspected of Causing Cancer.
H373: May Cause Damage to Organs Through Prolonged or Repeated Exposure.
H401: Toxic to Aquatic Life.
H413: May Cause Long Lasting Harmful Effects to Aquatic Life.

Appearance: Dispersion **Physical State**: Liquid **Odor**: No information available

Precautionary Statements – Prevention

P203: Obtain, read and follow all safety instructions before use.
P210: Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ ventilating equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P261: Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264+P265: Wash hands and arms thoroughly after handling. Do not touch eyes.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.

Precautionary Statements – Response

P301+P316: IF SWALLOWED: Get emergency medical help immediately.
P301+P317: IF SWALLOWED: Get medical help.
P302+P352: IF ON SKIN: wash with plenty of water and soap.
P303+P361+P353: IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water [or shower].
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
P317: Get emergency medical help.
P318: If exposed or concerned, get medical advice.
P319: Get medical help if you feel unwell.
P331: Do NOT induce vomiting.
P337+P317: If eye irritation persists: Get medical help.
P361+P364: Take off immediately all contaminated clothing and wash it before reuse.

P370+P378: In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish.

Precautionary Statements - Storage

P403+P233+P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405: Store locked up.

Precautionary Statements – Disposal

P501: Dispose of contents and container in accordance with local/ regional/ national regulations.

Hazards Not Otherwise Classified (HNOC)

None known.

SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS

Mixture (Weight percentage varies with color)

Chemical Name	CAS No.	% (by Weight)	
Mn Compound 32	Proprietary	varies	*
Poly(oxy-1,2-ethanediyl), α-[bis(1-phenylethyl)phenyl] -.omega.-hydroxy-	Proprietary	varies	*
Tristyryl phenol-polyethylene glycol-phosphoric acid ester	Proprietary	varies	*
Xylene	1330-20-7	varies	*
Solvent Naptha (Petroleum), Light Aromatic	64742-95-6	varies	*
Psuedocumene (1,2,4-Trimethylbenzene)	95-63-6	varies	*
Cumene	98-82-8	varies	*
Ethylbenzene	100-41-4	varies	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4: FIRST-AID MEASURES

Description of First Aid Measures

General Advice Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/ doctor if you feel unwell.

Skin Contact IF ON SKIN (or hair): Wash contact areas with plenty of soap and water. Remove contaminated clothing and shoes. Launder contaminated clothing before reuse. If skin irritation or allergic reaction occurs: Get medical attention.

Eye Contact IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Do not rub the affected area. If irritation occurs, get medical assistance.

Ingestion IF SWALLOWED: Do not induce vomiting. Clean mouth with water and drink afterwards plenty of water. Call a physician immediately.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation.

Indication of need for immediate medical attention and special treatment

Note to physicians If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use dry sand, alcohol-resistant foam, dry chemical or carbon dioxide.

Special Protective Equipment for Firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Specific hazards arising from the chemical

Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous Combustion Products

Thermal decomposition and burning may produce carbon monoxide, carbon dioxide, nitrogen oxides, and other toxic compounds. Incomplete combustion products, Smoke, Fume, Oxides of carbon.

Explosion Data – Sensitivity to Mechanical Impact

None

Explosion Data – Sensitivity to Static Discharge

None

Special protective equipment for first responders

Wear self-contained breathing apparatus and protective suit.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required.
Keep unnecessary personnel away. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Extinguish all flames in the vicinity. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Local authorities should be advised if significant spills cannot be contained. Ventilate closed spaces before entering. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the SDS for Personal Protective Equipment.

Methods and material for containment and cleaning up

Contain spillage, collect runoff water. Keep out of drains, sewers, ditches, and waterways. Absorb with non-combustible material and transfer to properly labeled containers for later disposal.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Keep out of the reach of children. Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials, food and drink. Store locked up. Eliminate all ignition

sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. The pressure in sealed containers can increase under the influence of heat. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: EXPOSURE CONTROLS – PERSONAL PROTECTION

Control parameters

Exposure Limits Product may contain one or more of the following components:

Components	CAS	ACGIH TLV	OSHA PEL	NIOSH IDLH
Mn Compound 32 10 - < 20	n/a	TWA: 0.02 mg/m3 Mn respirable particulate matter TWA: 0.1 mg/m3 Mn inhalable particulate matter	(vacated) Ceiling: 5 mg/m3 Ceiling: 5 mg/m3 Mn	IDLH: 500 mg/m3 Mn TWA: 1 mg/m3 Mn STEL: 3 mg/m3 Mn
Titanium Dioxide 50-<65	13463-67-7	TWA: 0.2 mg/m3 nanoscale respirable particulate matter TWA: 2.5 mg/m3 finescale respirable particulate matter	TWA: 15 mg/m3 total dust (vacated) TWA: 10 mg/m3 total dust	IDLH: 5000 mg/m3 TWA: 2.4 mg/m3 CIB 63 fine
Cumene	98-82-8	TWA 50 ppm	TWA 245 mg/m3 50 ppm	
Pseudocumene (1,2,4-Trimethylbenzene)	95-63-6	TWA 25 ppm		
Solvent Naptha (Petroleum), Light Aromatic	64742-95-6	TWA 50 ppm	245 mg/m3 50 ppm	
Xylene	1330-20-7	TWA 100 ppm STEL 150 ppm		
Ethylbenzene	100-41-4	TWA 100 ppm STEL 125 ppm		

Appropriate engineering controls

Engineering controls Showers. Eyewash stations. Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye and face protection Safety glasses/goggles.

Skin and body protection	Protective gloves. Wear suitable protective clothing.
Respiratory protection	No protective equipment is needed under normal use conditions.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	**Odor**	No data available
Appearance	Dispersion	**Odor Threshold**	No data available
Color	Varies with selection		

Property	**Values**	**Remarks/Method**
pH	Not Available	
Melting point/freezing point	No data available	
Boiling point/Boiling range	> 136° C / 277° F	
Flash point	> 25° C / 77° F	CC (closed cup)
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit:	7%	
Lower flammability limit:	1%	
Lower explosion limit	No data available	
Upper explosion limit	No data available	
Vapor pressure	No data available	
Vapor density	No data available	
Relative density	Varies with selection	
Water solubility	No data available	
Solubility in other solvents	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidizing properties	No data available	

Other Information

Softening point	No data available
Molecular weight	No data available
VOC Content (%)	Not relevant

SECTION 10: STABILITY AND REACTIVITY

Reactivity
Flammable liquid and vapor.

Chemical stability
Stable under normal conditions.

Possibility of Hazardous Reactions
None under normal processing.

Conditions to avoid
Direct heating, dirt, chemical contamination, sunlight, UV or ionizing radiation, freezing temperatures. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

Incompatible materials
Strong acids. Strong bases. Strong oxidizing agents.

Hazardous Decomposition Products
Thermal decomposition can lead to release of irritating and toxic gases and vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

May contain one or more of the following components

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium Dioxide 13463-67-7	> 2000 mg/kg (Rat)		> 5.09 mg/L (Rat) 4 h
Trimethylolpropane 77-99-6	= 14100 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	> 0.85 mg/L (Rat) 4 h
Petroleum Naptha, Light Aromatic 64742-95-6	3492 mg/kg (Rat)	>3160 mg/kg (Rabbit)	
Xylene 1330-20-7	4300 mg/kg (Rat)	14100 uL/kg (Rabbit)	4550 ppm (Rat), 4h
Ethylbenzene 100-41-4	3500 mg/kg (Rat)	17800 uL/kg (Rabbit)	
Cumene 98-82-8	>2000 mg/kg (Rat)	10578 mg/kg (Rabbit)	40 mg/L (Rat), 4h
Pseudocumene (1,2,4-Trimethylbenzene) 95-63-6	6000 mg/kg (Rat)	3440 mg/kg (Rat)	10.2 mg/L (Rat), 4h

Additional Information

Inhalation	May cause respiratory irritation. Specific test data not available.
Eye Contact	Causes serious eye irritation, including itching, burning, redness, and tearing. Specific test data not available.
Ingestion	May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Specific test data not available.
Skin Contact	Causes skin irritation. Specific test data not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Reproductive Effects	Not Available
Teratogenicity	Not Available
Mutagenicity	Not Available
Embryotoxicity	Not Available
Sensitization to Product	Not Available
Synergistic Products	Not Available
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. May contain Titanium Dioxide 13463-67-7: ACGIH A3; IARC Group 2B; OSHA Present

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity Toxic to aquatic life with long-lasting effects. May contain one or more of the following components

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Trimethylolpropane 77-99-6				EC50: =13000mg/L (48h, Daphnia species) EC50: 10330 - 16360mg/L (48h, Daphnia magna)
Petroleum Naptha, Light Aromatic 64742-95-6	EC50: 2.9 mg/L			Daphnia 1: 3.2 mg/L
1,2,4-Trimethylbenzene 95-63-6		LC50: 7.72 (96h flow through, Pimephales promelas)		
Xylene 1330-20-7		LC50 13.40 (96h flow through) 23.53-29.97 (96h static)		

		Pimephales promelas) 2.66-4.09 (96h static) 13.5-17.3 (96h) Oncorhynchus mykiss 13.1-16.5 (96h flow through) 19 (96h) Lepomis macrochirus 780 (96h semi-static) 780 (96h) Cyprinus carpio 30.26-40.75 (96h static) Poecilia reticulata		
Cumene 98-82-8		4.8 (96h flow through) Orcorhynchus mykiss		Daphnia 1: 2.14 mg/L 48h

Persistence and Degradability Information not available

Other Adverse Effects Information not available

BioAccumulation May contain one or more of the following components

Chemical Name	Partition Coefficient
Trimethylolpropane 77-99-6	-0.47
1,2,4-Trimethylbenzene 95-63-6	3.04
Xylene 1330-20-7	2-3
Cumene 98-82-8	2.946

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

This material and its container must be disposed of as hazardous waste. Dispose in accordance with all local regulations and requirements. Do not allow this material to spill and runoff and contact with soil, waterways, drains and sewers. Do not reuse container. This product contains one or more substances that are listed with the State of California as a hazardous waste.

SECTION 14: TRANSPORTATION INFORMATION

DOT UN1263, Paint, 3, III

IATA UN1263, Paint, 3, III

IMDG UN1263, Paint, 3, III

IATA and IMDG information offered as a guide only. Specific regulations should be reviewed prior to placing the material into transportation.

SECTION 15: REGULATORY INFORMATION

All components of this product are designated as "active" on the TSCA Inventory or are not required to be listed.

US Federal Regulations

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Benzene [as part of xylene] (CAS 71-43-2)
Cumene (CAS 98-82-8)
Cancer, Central nervous system, Blood, Aspiration, Skin, Eye, Respiratory tract irritation, Flammability

SARA 313

Xylene CAS 1330-20-7
Ethylbenzene (CAS 100-41-4)
Cumene (CAS 98-82-8)
Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

Hazardous substance, Priority and Toxic pollutant

CERCLA

Xylene (CAS 1330-20-7) listed
Ethylbenzene (CAS 100-41-4) listed
Cumene (CAS 98-82-8) listed

US State Regulations

California Proposition 65

Benzene [as part of Xylene] (CAS 71-43-2)
Ethylbenzene (CAS 100-41-4)
Cumene (98-82-8)
(Product does not contain Titanium Dioxide in powder form, and it is not expected that Titanium Dioxide particles of respirable size would be generated during normal use of this product.)

US State Right To Know Regulations

Massachussetts Right To Know Components

Titanium Dioxide 13463-67-7
Xylene (CAS 1330-20-7)
Benzene [as part of Xylene] (CAS 71-43-2)
Ethylbenzene (CAS 100-41-4)

Pennsylvania Right To Know Components

Titanium Dioxide 13463-67-7
Xylene (CAS 1330-20-7)
Benzene [as part of Xylene] (CAS 71-43-2)
Ethylbenzene (CAS 100-41-4)
Cumene (CAS 98-82-8)
Naptha (petroleum), heavy alkylate (CAS 64741-65-7
Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

Rhode Island Right To Know Components

Xylene (CAS 1330-20-7)
Benzene [as part of Xylene] (CAS 71-43-2)
Ethylbenzene (CAS 100-41-4)
Cumene (CAS 98-82-8)
Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

New Jersey Right To Know Components

Titanium Dioxide 13463-67-7
Xylene (CAS 1330-20-7)
Benzene [as part of Xylene] (CAS 71-43-2)
Ethylbenzene (CAS 100-41-4)
Cumene (CAS 98-82-8)
Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)
Naptha (petroleum), heavy alkylate (CAS 64741-65-7)

SECTION 16: OTHER INFORMATION

NFPA Class IC Liquid: Flash Point above 73° F and below 100° F

Issue Date	February 1, 2026
Revision Date	Not relevant
Revision Note	None

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

END OF SAFETY DATA SHEET