

**SECTION 1: PRODUCT IDENTIFICATION**

<b>Product Name:</b>	DV-30
<b>Synonyms:</b>	
<b>Product Number:</b>	30-DV30-1G (1-gallon jug), 30-DV30-5G (5-gallon pail)
<b>Company:</b>	Durável
<b>Address:</b>	1212-A Graphic Ct., Charlotte NC 28206
<b>Business Phone:</b>	(704) 837-7991
<b>Emergency Phone:</b>	Chemtrec US (800) 424-9300 CNN 874540
<b>Date of Current Revision:</b>	December 1, 2022

**SECTION 2: HAZARD IDENTIFICATION**

**Classification of the Substance or Mixture**

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Highly Flammable Liquid and Vapor, H225	Category 2
Aspiration Hazard, H304	Category 1
Acute Toxicity, Dermal, H312	Category 4
Acute Toxicity, Inhalation, H332	Category 4
Skin Corrosion/ Irritation, H316	Category 2
Serious Eye Damage/ Eye Irritation, H319	Category 2B
Carcinogenicity, H351	Category 2
Specific Target Organ Toxicity, Single Exposure (Respiratory Tract Irritation), H373	Category 3
Specific Target Organ Toxicity, Single Exposure (Narcotic Effects)	Category 3
Hazardous to the Aquatic Environment, Acute Hazard, H401	Category 2
Chronic Aquatic Toxicity, H411	Category 2

**EMERGENCY OVERVIEW:** This product is a clear liquid.

Signal Word: **DANGER**

**Hazard Statements**

H225: Highly flammable liquid and vapor.  
H304: May be fatal if swallowed and enters airways.  
H312 + H332: Harmful in contact with skin or inhaled.  
H315: Causes skin irritation.  
H335: May cause respiratory irritation.  
H336: May cause drowsiness or dizziness.  
H351: Suspected of causing cancer.  
H373: May cause damage to organs through prolonged or repeated exposures.  
H411: Toxic to aquatic life with long lasting effects.

**Precautionary Statements****General**

P102: Keep out of reach of children.

P103: Read carefully and follow all instructions

**Prevention**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces. -- No smoking.

P233: Keep container tightly closed.

P240: Ground / bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, and lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapors/ spray.

P261: Avoid breathing mist / vapors.

P264: Wash skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Response**

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308 + P313: If exposed or concerned: Get medical advice/ attention.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P331: DO NOT induce vomiting.

P332 + P313: If skin irritation occurs: Get medical advice/ attention.

P370 + P378: In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish.

P391: Collect spillage.

**Storage**

P403 + P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

**Disposal**

P501: Dispose of contents and container in accordance with local regulations.

**SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS**

**Substance**

This material is regulated as a mixture

Chemical Name	CAS No.	EC No.	% (by Weight)
Xylene	1330-20-7	215-535-7	<34
Ethylbenzene	100-41-4	NE	<12
Solvent Naptha (Petroleum), Light Aromatic	64742-95-6	265-192-2	<15
Cumene	98-82-8	NE	<7
Psuedocumene (1,2,4-Trimethylbenzene)	95-63-6	NE	<15
Naptha (petroleum), Heavy Alkylate	64741-65-7	NE	<5
Dimethyl Carbonate	616-38-6	210-478-4	<4
Non-Hazardous, Trade Secret			<38

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**SECTION 4: FIRST-AID MEASURES**

**Description of First Aid Measures**

**General Advice**

Move out of the dangerous area. Consult a physician. Provide this Safety Data Sheet to the doctor in attendance.

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance.

**Skin Contact**

IF ON SKIN (or hair): Wash contact areas with plenty of soap and water. Remove contaminated clothing and shoes. Launder contaminated clothing before reuse. Get medical attention.

**Eye Contact**

IF IN EYES: Immediately flush eyes with plenty of water for 10 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. If irritation occurs, get medical assistance.

**Ingestion**

IF SWALLOWED: Seek immediate medical attention. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

**Note to Physician**

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

**SECTION 5: FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Foam, CO2, Dry chemical, water spray or fog.

**Unsuitable extinguishing media**

Do not use water jet.

**Specific hazards arising from the substance or mixture**

Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

**Hazardous combustion products**

Incomplete combustion products, Smoke, Fume, Oxides of carbon.

**Explosion Data****Sensitivity to Mechanical Impact**

Not available

**Sensitivity to Static Discharge**

Not available

**Protective equipment and precautions for firefighters**

Evacuate area. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel. Move containers from fire area if this can be done without risk.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Extinguish all flames in the vicinity. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Local authorities should be advised if significant spills cannot be contained. Ventilate closed spaces before entering. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the SDS for Personal Protective Equipment.

**Methods and material for containment and cleaning up**

**Large Spills** Stop the flow of material, if this is without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements, or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

**Small Spills** Stop the flow of material, if this is without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Disposal according to local regulations.

**SECTION 7: HANDLING AND STORAGE****Precautions for safe handling**

Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Conditions for safe storage, including any incompatibilities**

Keep out of the reach of children. Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials, food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. The pressure in sealed containers can increase under the influence of heat. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

**SECTION 8: EXPOSURE CONTROLS – PERSONAL PROTECTION**

**Exposure Limit Values**

<b>Component</b>	<b>Value / Source</b>			
Cumene	TWA	245 mg/m3	50 ppm	OSHA Z1
Cumene	TWA	No data available	50 ppm	ACGIH
Pseudocumene (1,2,4-Trimethylbenzene)	TWA	No data available	25 ppm	ACGIH
Solvent Naptha (Petroleum), Light Aromatic	TWA	100 mg/m3	19 ppm	Exxon Mobile
Xylene	PEL	435 mg/m3	100 ppm	OSHA Z1
Xylene	TWA	435 mg/m3	100 ppm	ACGIH
Xylene	STEL	No data available	150 ppm	ACGIH
Ethylbenzene	PEL	435 mg/m3	100 ppm	OSAH Z1
Ethylbenzene	TWA	No data available	20 ppm	ACGIH

**Occupational Exposure Controls**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures should provide adequate ventilation so that exposure limits are not exceeded. Use explosion-proof ventilation equipment.

**Appropriate engineering controls**

**Exposure Controls**

Air contaminant levels should be controlled below the PEL or TLV for this product (see Exposure Guidelines).

**Individual protection measures, such as personal protective equipment**

<b>Eye and face protection</b>	Safety glasses with side shields or full face shield should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or gases.
<b>Skin and body protection</b>	Chemical-resistant, nitrile gloves standard should be worn at all times. Appropriate footwear and any additional skin protection measures such as long-sleeved clothing to minimize skin contact.
<b>Respiratory protection</b>	Wear suitable NIOSH approved respirator when ventilation is not adequate.
<b>Hygienic measures</b>	Wash hands and exposed skin thoroughly after handling chemical products, before eating, smoking, and using the lavatory and at the end of the working period. Contaminated clothing should be removed promptly. Wash contaminated clothing before reusing.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid	<b>Odor</b>	Aromatic, Solvent-Like
<b>Appearance</b>	Colorless Liquid	<b>Odor Threshold</b>	No data available
<b>Color</b>	Colorless		

<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks/Method</u></b>
<b>pH</b>	Not Available	
<b>Melting point/freezing point</b>	-26.1 °C (-15 °F)	
<b>Boiling point/Boiling range</b>	90 °C (194 °F)	
<b>Flash point</b>	18 °C (65 °F)	
<b>Evaporation rate</b>	Not Available	
<b>Flammability (solid, gas)</b>	Not Available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	7%	
<b>Lower flammability limit:</b>	1%	
<b>Vapor pressure</b>	Not Available	
<b>Vapor density</b>	Not Available	
<b>Relative density</b>	Not Available	
<b>Water solubility</b>	Very slightly soluble	
<b>Solubility in other solvents</b>	Not Available	
<b>Partition coefficient</b>	Not Available	
<b>Autoignition temperature</b>	Not Available	

<b>Decomposition temperature</b>	Not Available
<b>Kinematic viscosity</b>	Not Available
<b>Dynamic viscosity</b>	Not Available
<b>Explosive properties</b>	Not Available
<b>Oxidizing properties</b>	Not Available

**Other Information**

<b>Softening point</b>	Not Relevant
<b>Molecular weight</b>	Not Available
<b>VOC Content (%)</b>	<600 g/L
<b>Density</b>	Not Available
<b>Bulk Density</b>	Not Available

**SECTION 10: STABILITY AND REACTIVITY****Reactivity**

Not available

**Chemical stability**

The product is stable

**Possibility of Hazardous Reactions**

Hazardous reactions will not occur under normal conditions

**Conditions to avoid**

Heat, flames and sparks. Ignition sources. Contact with incompatible materials. Do not pressurize, cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

**Incompatible materials**

Oxidizing materials

**Hazardous Decomposition Products**

Hazardous decomposition products should not be produced under normal conditions.



**SECTION 11: TOXICOLOGICAL INFORMATION**

Information on toxicological effects

<b>Chemical Name</b>	<b>Oral LD50</b>	<b>Dermal LD50</b>	<b>Inhalation LC50</b>
Petroleum Naptha, Light Aromatic 64742-95-6	8400 mg/kg (Rat)	>2000 mg/kg (Rabbit)	>5.2 mg/L, 3400 ppm, 4h
1,2,4-Trimethylbenzene 95-63-6	5000 mg/kg (Rat)	No data available	18 mg/L (Rat), 4h
Xylene 1330-20-7	4300 mg/kg (Rat)	>1700 mg/kg (Rabbit)	47.6 g/L, 5000 ppm (Rat), 4h
Dimethyl Carbonate 616-38-6	5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	5.36 mg/L (Rat), 4h
Cumene 98-82-8	1400 mg/kg (Rat)	>3160 mg/kg (Rabbit)	39 mg/L (Rat), 4h

Additional Information

<b>Inhalation</b>	No known significant effects or critical hazards
<b>Eye Contact</b>	Causes serious eye irritation, including itching, burning, redness, and tearing.
<b>Ingestion</b>	May be fatal if swallowed and enters airways.
<b>Skin Contact</b>	No specific data

Potential Chronic Health Effects

<b>General</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Carcinogenicity</b>	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
<b>Mutagenicity</b>	No known significant effects or critical hazards.
<b>Teratogenicity</b>	No known significant effects or critical hazards.
<b>Developmental Effects</b>	No known significant effects or critical hazards.
<b>Fertility Effects</b>	No known significant effects or critical hazards.

**SECTION 12: ECOLOGICAL INFORMATION**

**Eco Toxicity**

Toxic to aquatic life with long-lasting effects.

**Toxicity to Fish**

Chemical Name	Species	LC50 (mg/L)	Exposure (Method)
Petroleum Naptha, Light Aromatic 64742-95-6	Oncorhynchus mykiss	9.22	96h
1,2,4-Trimethylbenzene 95-63-6	Pimephales promelas	7.72	96h (flow-through)
Xylene 1330-20-7	Pimephales promelas	13.40	96h (flow-through)
	Pimephales promelas	25.53-29.97	96h (static)
	Oncorhynchus mykiss	2.66-4.09	96h
	Lepomis macrochirus	19.00	96h
	Lepomis macrochirus	13.10-16.50	96h (flow-through)
	Lepomis macrochirus	7.71-9.59	96h (static)
	Poecilia reticulata	30.26-40.75	96h (static)
Dimethyl Carbonate 616-38-6	Danio rerio	>= 100 mg/L	96h (flow-through)
Cumene 98-82-8	Pimephales promelas	6.04-6.61	96h (flow-through)
	Orcorhynchus mykiss	4.80	96h (flow-through)
	Orcorhynchus mykiss	2.70	96h (semi-static)
	Poecilia reticulata	5.10	96h (semi-static)

Chemical Name	Algae/ Aquatic Plants EC50	Microorganisms EC50	Crustacea EC50
Petroleum Naptha, Light Aromatic 64742-95-6	Pseudokirchneriella subcapitata 3.1 mg/L 72h	No data available	Daphnia magna 6.14 mg/L 48h
1,2,4- Trimethylbenzene 95-63-6	No data available	No data available	Daphnia magna 3.60 mg/L 48h
Xylene 1330-20-7	Pseudokirchneriella subcapitata 72 mg/L 14d	0.0084 mg/L 24h	Daphnia magna 3.82 mg/L 48h Gammarus lacustris 0.6 mg/L 48h
Dimethyl Carbonate 616-38-6	Pseudokirchneriella subcapitata >100 mg/L 72h (static)	>1000 mg/L 3h	Daphnia magna >100 mg/L 48h (static)
Cumene 98-82-8	Pseudokirchneriella subcapitata 2.6 mg/L 72h	0.89 mg/L 5 min 1.10 mg/L 15 min 1.48 mg/L 30 min 172 mg/L 24h	Daphnia magna 7.9-14.1 mg/L 48h

**Persistence and degradability**

Dimethyl Carbonate 616-38-6 aerobic – Exposure time 28d – Result: 86% - Readily biodegradable (OCED Test Guideline 301C)

**Bioaccumulation**

No data available

**Mobility in Soil**

Chemical Name	Partition Coefficient (log POW)
Petroleum Naptha, Light Aromatic 64742-95-6	3.42
1,2,4-Trimethylbenzene 95-63-6	3.63
Xylene 1330-20-7	2.77-3.15
Cumene 98-82-8	3.55

**Other adverse effects**

No known significant effects or critical hazards.

**SECTION 13: DISPOSAL CONSIDERATIONS****Waste treatment methods**

This material and its container must be disposed of as hazardous waste. Dispose in accordance with all local regulations and requirements. Do not allow this material to spill and runoff and contact with soil, waterways, drains and sewers.

**SECTION 14: TRANSPORTATION INFORMATION****DOT**

<b>UN/ID no.</b>	1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Special Precautions</b>	Not available

**IMDG**

<b>UN/ID no.</b>	1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Environmental Hazards</b>	Marine Pollutant: No
<b>Special Precautions</b>	Not available

**IATA**

<b>UN/ID no.</b>	1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Environmental Hazards</b>	No
<b>Special Precautions</b>	Not available

**SECTION 15: REGULATORY INFORMATION****US Federal Regulations**

This product is hazardous according to OSHA 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Benzene [as part of xylene] (CAS 71-43-2)  
Cumene (CAS 98-82-8)  
Cancer, Central nervous system, Blood, Aspiration, Skin, Eye, Respiratory tract irritation,  
Flammability

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Xylene (CAS 1330-20-7) listed  
Ethylbenzene (CAS 100-41-4) listed  
Cumene (CAS 98-82-8) listed

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Hazard Categories**

Immediate Hazard – Yes  
Delayed Hazard – Yes  
Fire Hazard – Yes  
Pressure Hazard – No  
Reactivity Hazard - No

**SARA 302 Extremely Hazardous Substance**

Not listed

**SARA 311/312 Hazardous chemical**

No

**SARA 313 (TRI reporting)**

Xylene CAS 1330-20-7  
Ethylbenzene (CAS 100-41-4)  
Cumene (CAS 98-82-8)  
Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Xylene (CAS 1330-20-7)  
Ethylbenzene (CAS 100-41-4)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated

**Clean Water Act (CWA) Section 112(r) (40 CFR 68.130)**

Hazardous substance, Priority and Toxic pollutant

**Safe Drinking Water Act (SDWA)**

0 mg/l 0.005 mg/l

**Massachusetts Right To Know Components – Substance List**

Xylene (CAS 1330-20-7)  
Benzene (CAS 71-43-2)  
Ethylbenzene (CAS 100-41-4)

**US. New Jersey Worker and Community Right-to-Know Act**

Xylene (CAS 1330-20-7)  
Benzene (CAS 71-43-2)  
Ethylbenzene (CAS 100-41-4)  
Cumene (CAS 98-82-8)  
Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Xylene (CAS 1330-20-7)  
Benzene (CAS 71-43-2)  
Ethylbenzene (CAS 100-41-4)  
Cumene (CAS 98-82-8)  
Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

**US. Rhode Island Right-to-Know**

Xylene (CAS 1330-20-7)  
Benzene (CAS 71-43-2)  
Ethylbenzene (CAS 100-41-4)  
Cumene (CAS 98-82-8)  
Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

**US. California Proposition 65**

Carcinogens & Reproductive Toxicity (CRT): Listed substance

Benzene (CAS 71-43-2)  
Ethylbenzene (CAS 100-41-4)

**SECTION 16: OTHER INFORMATION**

<b>NFPA</b>	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
<b>HMS</b>	Health hazards 2	Flammability 2	Physical hazards 2	Personal Protection

**Issue Date** December 1, 2022

**Revision Date** Not applicable

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

**END OF SAFETY DATA SHEET**