

SECTION 1: PRODUCT IDENTIFICATION

Product Name: First Day Low
Synonyms:
Product Number: 30-FDL-5G
Company: Durável
Address: 225 Olympic St., Charlotte NC 28273
Business Phone: (704) 837-7991
Emergency Phone: Chemtrec US (800) 424-9300 CNN 1014580
Date of Current Revision: May 4, 2024

SECTION 2: HAZARD IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Highly Flammable Liquid and Vapor, H225	Category 2
Aspiration Hazard, H304	Category 1
Acute Toxicity, Dermal, H312	Category 3
Skin Corrosion/ Irritation, H315	Category 2
Serious Eye Damage/ Eye Irritation, H319	Category 2A
Acute Toxicity, Inhalation, H332	Category 4
Specific Target Organ Toxicity, Single Exposure (Respiratory Tract Irritation), H335	Category 3
Specific Target Organ Toxicity, Single Exposure (Narcotic Effects), H336	Category 3
Carcinogenicity, H351	Category 2
Specific Target Organ Toxicity, Single Exposure (Central Nervous System), H371	Category 2
Specific Target Organ Toxicity, Repeated Exposure (Kidney, Liver, Spleen, Blood). H373	Category 2

EMERGENCY OVERVIEW: This product is a clear liquid.

Signal Word: **DANGER**

Hazard Statements
H225: Highly flammable liquid and vapor.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.
H371: May cause damage to organs.
H373: May cause damage to organs through prolonged or repeated exposures.



Precautionary Statements

General

P102: Keep out of reach of children.

Prevention

P203: Obtain, read and follow all safety instructions before use.

P210: Keep away from heat, hot surface, sparks, open flames and other ignition sources.

No smoking.

P233: Keep container tightly closed.

P240: Ground/ bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, and lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P261: Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 + P265: Wash skin thoroughly after handling. Do not touch eyes.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P301 + P316: IF SWALLOWED: Get emergency medical help immediately.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P316: IF Exposed or concerned: Get emergency medical help immediately.

P319: Get medical help if you feel unwell.

P331: DO NOT induce vomiting.

P332 + P317: IF SKIN irritation occurs: Get emergency medical help.

P337 + P317: If eye irritation persists: Get emergency medical help.

P362 + P364: Take off contaminated clothing and wash it before reuse.

P370 + P378: In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish.

Storage

P403 + P233 + P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405: Store locked up.

Disposal

P501: Dispose of contents and container in accordance with local regulations.

SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS

Substance

This material is regulated as a mixture

Chemical Name	CAS No.	EC No.	% (by Weight)
Solvent Naptha (Petroleum), Light Aromatic	64742-95-6	265-192-2	30-45%
Acetone	67-64-1		30-45%
Cumene	98-82-8	NE	5-10%
Psuedocumene (1,2,4-Trimethylbenzene)	95-63-6	NE	1-5%
Mixed Xylenes	1330-20-7	215-535-7	1-5%
Non-Hazardous, Trade Secret			20-30%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4: FIRST-AID MEASURES

Description of First Aid Measures

General Advice

Move out of the dangerous area. Consult a physician. Provide this Safety Data Sheet to the doctor in attendance.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance.

Skin Contact

IF ON SKIN (or hair): Wash contact areas with plenty of soap and water. Remove contaminated clothing and shoes. Launder contaminated clothing before reuse. Get medical attention.

Eye Contact

IF IN EYES: Immediately flush eyes with plenty of water for 10 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. If irritation occurs, get medical assistance.

Ingestion

IF SWALLOWED: Seek immediate medical attention. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Note to Physician

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION 5: FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Foam, CO₂, Dry chemical, water spray or fog.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the substance or mixture

Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous combustion products

Incomplete combustion products, Smoke, Fume, Oxides of carbon.

Explosion Data**Sensitivity to Mechanical Impact**

Not available

Sensitivity to Static Discharge

Not available

Protective equipment and precautions for firefighters

Evacuate area. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel. Move containers from fire area if this can be done without risk.

SECTION 6: ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Extinguish all flames in the vicinity. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Local authorities should be advised if significant spills cannot be contained. Ventilate closed spaces before entering. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the SDS for Personal Protective Equipment.

Methods and material for containment and cleaning up

- Large Spills** Stop the flow of material, if this is without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements, or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
- Small Spills** Stop the flow of material, if this is without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Disposal according to local regulations.

SECTION 7: HANDLING AND STORAGE**Precautions for safe handling**

Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities

Keep out of the reach of children. Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials, food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. The pressure in sealed containers can increase under the influence of heat. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: EXPOSURE CONTROLS – PERSONAL PROTECTION

Exposure Limit Values

Component	Value / Source			
Acetone	TWA	500 ppm 8 hours	1500 ppm 15 min	STEL 1500
Acetone	TWA	1000 ppm		OSHA PEL
Acetone	TWA	2400 mg/m3 (vacated)		OSHA PEL
Acetone	TWA	750 ppm (vacated)		OSHA PEL
Acetone	TWA	1800 mg/m3 (vacated)		OSHA PEL
Acetone	STEL	2400 mg/m3		OSHA PEL
Acetone	IDLH	2500 ppm		NIOSH IDLH
Acetone	TWA	250 ppm		NIOSH IDLH
Acetone	TWA	590 mg/m3		NIOSH IDLH
Cumene	TWA	245 mg/m3	50 ppm	OSHA Z1
Cumene	TWA	No data available	50 ppm	ACGIH
Pseudocumene (1,2,4-Trimethylbenzene)	TWA	No data available	25 ppm	ACGIH
Solvent Naptha (Petroleum), Light Aromatic	TWA	100 mg/m3	19 ppm	Exxon Mobile
Xylene	PEL	435 mg/m3	100 ppm	OSHA Z1
Xylene	TWA	435 mg/m3	100 ppm	ACGIH
Xylene	STEL	No data available	150 ppm	ACGIH

Occupational Exposure Controls

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures should provide adequate ventilation so that exposure limits are not exceeded. Use explosion-proof ventilation equipment.

Individual protection measures, such as personal protective equipment

Eye and face protection	Safety glasses with side shields or full face shield should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or gases.
Skin and body protection	Chemical-resistant, nitrile gloves standard should be worn at all times. Appropriate footwear and any additional skin protection measures such as long-sleeved clothing to minimize skin contact.
Respiratory protection	Wear suitable NIOSH approved respirator when ventilation is not adequate.
Hygienic measures	Wash hands and exposed skin thoroughly after handling chemical products, before eating, smoking, and using the lavatory and at the end of the working period. Contaminated clothing should be removed promptly. Wash contaminated clothing before reusing.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Aromatic, Solvent-Like
Appearance	Colorless Liquid	Odor Threshold	No data available
Color	Colorless		
<u>Property</u>	<u>Values</u>	<u>Remarks/Method</u>	
pH	Not Available		
Melting point/freezing point	-94° C (-137° F)		
Boiling point/Boiling range	56° C (133° F)		
Flash point	-17° C (1.4 °F)	Closed cup	
Evaporation rate	Not Available		
Flammability (solid, gas)	Not Available		
Flammability Limit in Air			
Upper flammability limit:	Not Available		
Lower flammability limit:	Not Available		
Vapor pressure	Not Available		
Vapor density	Not Available		

Relative density	0.86
Water solubility	Very slightly soluble
Solubility in other solvents	Not Available
Partition coefficient	Not Available
Autoignition temperature	Not Available
Decomposition temperature	Not Available
Kinematic viscosity	Not Available
Dynamic viscosity	Not Available
Explosive properties	Not Available
Oxidizing properties	Not Available

Other Information

Softening point	Not Relevant
Molecular weight	Not Available
VOC Content (%)	<600 g/L
Density	7.198
Bulk Density	Not Available

SECTION 10: STABILITY AND REACTIVITY**Reactivity**

Not available

Chemical stability

The product is stable

Possibility of Hazardous Reactions

Hazardous reactions will not occur under normal conditions

Conditions to avoid

Heat, flames and sparks. Ignition sources. Contact with incompatible materials. Do not pressurize, cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

Incompatible materials

Oxidizing materials, strong alkalis, strong acids

Hazardous Decomposition Products

Hazardous decomposition products should not be produced under normal conditions.
Hazardous decomposition products formed under fire conditions: carbon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Naptha, Light Aromatic 64742-95-6	8400 mg/kg (Rat)	>2000 mg/kg (Rabbit)	>5.2 mg/L, 3400 ppm, 4h
Acetone	-	-	50100 mg/m3 (Rat), 8h
1,2,4-Trimethylbenzene 95-63-6	5000 mg/kg (Rat)	No data available	18 mg/L (Rat), 4h
Xylene 1330-20-7	3523 mg/kg (Rat)	>1700 mg/kg (Rabbit)	29.09 g/L (Rat), 4h
Cumene 98-82-8	>2000 mg/kg (Rat)	10578 mg/kg (Rabbit)	40 mg/L (Rat), 4h

Additional Information

Inhalation	No known significant effects or critical hazards
Eye Contact	Causes serious eye irritation. Risk of serious damage to eyes.
Ingestion	May be fatal if swallowed and enters airways.
Skin Contact	Causes severe burns. Irritating to skin.

Potential Chronic Health Effects

General	May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental Effects	No known significant effects or critical hazards.
Fertility Effects	No known significant effects or critical hazards.

SECTION 12: ECOLOGICAL INFORMATION

Eco Toxicity

Toxic to aquatic life with long-lasting effects.

Toxicity to Fish

Chemical Name	Species	LC50 (mg/L)	Exposure (Method)
Petroleum Naptha, Light Aromatic	Oncorhynchus mykiss	9.22	96h

64742-95-6			
Acetone 67-64-1	Oncorhynchus mykiss	4.74-6.33	96h
	Pimephales promelas	6210-8120	96h
	Lepomis macrochirus	8300	96h (static)
1,2,4-Trimethylbenzene 95-63-6	Pimephales promelas	7.72	96h (flow-through)
Xylene 1330-20-7	Pimephales promelas	13.40	96h (flow-through)
	Pimephales promelas	25.53-29.97	96h (static)
	Oncorhynchus mykiss	2.66-4.09	96h
	Lepomis macrochirus	19.00	96h
	Lepomis macrochirus	13.10-16.50	96h (flow-through)
	Lepomis macrochirus	7.71-9.59	96h (static)
	Poecilia reticulata	30.26-40.75	96h (static)
Cumene 98-82-8	Pimephales promelas	6.04-6.61	96h (flow-through)
	Oncorhynchus mykiss	4.80	96h (flow-through)
	Oncorhynchus mykiss	2.70	96h (semi-static)
	Poecilia reticulata	5.10	96h (semi-static)

Chemical Name	Algae/ Aquatic Plants EC50	Microorganisms EC50	Crustacea EC50
Petroleum Naptha, Light Aromatic 64742-95-6	Pseudokirchneriella subcapitata 3.1 mg/L 72h	No data available	Daphnia magna 6.14 mg/L 48h
Acetone 6-64-1	No data available	No data available	Daphnia magna 10294-17704 48h
1,2,4- Trimethylbenzene 95-63-6	No data available	No data available	Daphnia magna 3.60 mg/L 48h
Xylene 1330-20-7	Pseudokirchneriella subcapitata 72 mg/L 14d	0.0084 mg/L 24h	Daphnia magna 3.82 mg/L 48h Gammarus lacustris 0.6 mg/L 48h
Cumene 98-82-8	Pseudokirchneriella subcapitata 2.6 mg/L 72h	0.89 mg/L 5 min 1.10 mg/L 15 min 1.48 mg/L 30 min 172 mg/L 24h	Daphnia magna 7.9-14.1 mg/L 48h

Persistence and degradability

No data available

Bioaccumulation

No data available

Mobility in Soil

Chemical Name	Partition Coefficient (log POW)
Petroleum Naptha, Light Aromatic 64742-95-6	3.42
Acetone 67-64-1	-0.24
1,2,4-Trimethylbenzene 95-63-6	3.63
Xylene 1330-20-7	2.77-3.15
Cumene 98-82-8	3.55

Other adverse effects

No known significant effects or critical hazards.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

This material and its container must be disposed of as hazardous waste. Dispose in accordance with all local regulations and requirements. Do not allow this material to spill and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: TRANSPORTATION INFORMATION

DOT

UN/ID no. 1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II
Special Precautions Not available

IMDG

UN/ID no. 1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II
Environmental Hazards Marine Pollutant: No

Special Precautions Not available

IATA

UN/ID no. 1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II
Environmental Hazards No
Special Precautions Not available

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

This product is hazardous according to OSHA 29 CFR 1910.1200.
 All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Benzene [as part of xylene] (CAS 71-43-2)
 Cumene (CAS 98-82-8)
 Cancer, Central nervous system, Blood, Aspiration, Skin, Eye, Respiratory tract irritation,
 Flammability

CERCLA Hazardous Substance List (40 CFR 302.4)

Xylene (CAS 1330-20-7) listed
 Cumene (CAS 98-82-8) listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories

Immediate Hazard – Yes
 Delayed Hazard – Yes
 Fire Hazard – Yes
 Pressure Hazard – No
 Reactivity Hazard - No

SARA 302 Extremely Hazardous Substance

Not listed

SARA 311/312 Hazardous chemical

Acute Health Hazard – Yes
 Chronic Health Hazard – Yes
 Fire Hazard – Yes
 Sudden Release of Pressure Hazard – Yes

Reactive Hazard – No

SARA 313 (TRI reporting)

Xylene CAS 1330-20-7

Cumene (CAS 98-82-8)

Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated

Clean Water Act (CWA) Section 112(r) (40 CFR 68.130)

Hazardous substance, Priority and Toxic pollutant.

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Safe Drinking Water Act (SDWA)

0 mg/l 0.005 mg/l

Massachusetts Right To Know Components – Substance List

Xylene (CAS 1330-20-7)

Benzene (CAS 71-43-2)

US. New Jersey Worker and Community Right-to-Know Act

Xylene (CAS 1330-20-7)

Benzene (CAS 71-43-2)

Cumene (CAS 98-82-8)

Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Xylene (CAS 1330-20-7)

Benzene (CAS 71-43-2)

Cumene (CAS 98-82-8)

Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

US. Rhode Island Right-to-Know

Xylene (CAS 1330-20-7)

Benzene (CAS 71-43-2)

Cumene (CAS 98-82-8)

Pseudocumene (1,2,4-Trimethylbenzene) (CAS 95-63-6)

US. California Proposition 65

Carcinogens & Reproductive Toxicity (CRT): Listed substance

Benzene (CAS 71-43-2)

Acetone (CAS 67-64-1)

SECTION 16: OTHER INFORMATION

NFPA Class IB Flammable Liquid: Flash Point below 73° F, Boiling Point above 100° F

Issue Date December 1, 2022

Revision Date May 4, 2024

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

END OF SAFETY DATA SHEET