

## Micronized Polymer Traction Additive

D-Grip micronized polymer traction additive provides increased slip-fall protection when added to a range of concrete floor coatings. There are two sizes: D-Grip (50 mesh), and D-Grip HD (20 mesh). D-Grip mixes easily into sealers and coatings and stays suspended with minimal additional stirring.

**SLIP-FALL PROTECTION**

### Typical Uses:

- Swimming Pool Decks
- Driveways and Sidewalks
- Stamped Concrete
- Patios and Garages
- Other Interior and Exterior Surfaces

### Product Advantages:

- Mixes Easily and Stays Suspended
- Only Slight Loss of Gloss
- Range of Sizes

### Available in two sizes

D-Grip - Standard 50 mesh  
D-Grip HD - Heavy Duty 20 mesh

### Packaging

30 Ounce Bottle

### Directions for Use:

### Mixing Instructions:

Shake container before measuring. Blend up to six ounces of D-Grip per gallon into topcoat prior to application. When used in single-component products D-Grip can be blended in the original sealer container. Two-component products should first be mixed for the time recommended on their TDS prior to adding D-Grip. Stir well without introducing air into the product. In larger volumes, it may be necessary to stir occasionally during application.

### Application Instructions:

When using a roller pan, make sure to roll along the bottom and edges of the roller tray. This action will help keep the material in suspension and evenly distributed on the roller nap surface. Roll sealer or coating per that product's TDS instructions. D-Grip additive is intended to be blended thoroughly in the topcoat prior to application. DO NOT attempt to broadcast D-Grip materials.

**FOR PROFESSIONAL USE ONLY**

# Technical Data Sheet

## Slip Resistance Disclaimer:

Notice: The Occupational Safety and Health Administration (OSHA) and the American Disabilities Act (ADA) have set enforceable standards for slip-fall protection on walking surfaces. The ADA standards are the more stringent and require a minimum coefficient of friction (CoF) on level walking surfaces of 0.6 and on ramped walking surfaces of 0.8. The system applicator / end user assumes all responsibility to provide a flooring system that meets all current safety standards. Neither Durável nor its selling agents will be responsible for any injury that may be incurred in a slip-fall accident. Furthermore, Durável recommends the use of slip-resistant aggregate in all coatings or floor systems that could possibly be exposed to wet conditions or become contaminated with oils, grease or other lubricants.

## Storage:

Store in a closed container.

## Disposal:

Disposal of product and packaging should be in accordance with applicable regional, national and local laws and regulations.

## Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature.

## Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet.

## Warranty:

Before using any Durável product, read and understand its accompanying Safety Data Sheet and Application Instructions for important safety information.

Standard Terms and Conditions of Sale, including Standard Warranty apply. Visit [Duravel.com](http://Duravel.com) for the latest version.

# Technical Data Sheet

## Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

## Safety Instructions:

These products are micronized powders.  
Static charges on the powders may ignite flammable atmospheres.  
High levels of product dust in the atmosphere may present a dust explosion hazard.

**IF IN EYES:** Immediately flush with copious amounts of water for at least 20 minutes.

If eye irritation persists: Get medical advice/ attention.

**IF SWALLOWED:** Immediately call a POISON CONTROL CENTER/ doctor. Do not induce vomiting.

Aspiration hazard. Dilute with 1-2 glasses of water. Get medical aid. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.

**IF ON SKIN (or hair):** Remove contaminated clothing. Wash skin thoroughly with soap and water.

If skin irritation occurs: Get medical advice or attention.

**IF INHALED:** Treat as a nuisance dust. Remove victim to fresh air and provide oxygen if breathing is difficult. Immediate medical attention not normally required. No delayed effects expected. Call a POISON CENTER/doctor if you feel unwell.



**Always Review SDS & Technical Data Prior to Use**