DURÁVEL®
Products for Professionals

D-Matte

Gloss Reduction Powder

D-Matte is a fine powder additive used to lower the gloss of clear concrete floor coatings. It can be used in both solvent-based and water-based systems, making it more versatile than many other gloss-reducing products.

D-Matte mixes easily into sealers and coatings and stays suspended well, with only minimal stirring needed during application.

Typical Uses:

- **Reduce Gloss in Clear Coatings**
- **Solvent Base Acrylic Sealers**
- **Water Base Acrylic Sealers**

Product Advantages :

- **Mixes Easily and Stays Suspended**
- **For Solvent and Water Base Sealers**
- **Adjustable Gloss Reduction**

Use in Solvent Base and Water Base Sealers

Packaged in One Pound Jars

ANTI-SLIP

Coverage:

For normal gloss reduction, add 1 full pound of D-Matte to 5 gallons of clear coating.

For a lower-gloss finish, add up to 1 additional pound of D-Matte per 5 gallons.

Technical Data

Directions for Use:

Mixing Instructions:

Shake the container before opening. Using a ribbon mixer, slowly blend D-Matte into the selected topcoat. Mix carefully to avoid pulling air into the coating.

When working from a paint tray, stir the product before each refill to keep the D-Matte evenly mixed.

D-Matte is not recommended for use with two-component products.

Application Instructions:

When using a roller pan, roll through the bottom and along the edges of the tray each time you load the roller. This helps keep D-Matte suspended and evenly distributed on the roller cover.

Apply the sealer or coating according to that product's TDS instructions.

D-Matte must be thoroughly mixed into the topcoat before application. Do not broadcast D-Matte onto the surface.

FOR PROFESSIONAL USE ONLY

Slip Resistance Disclaimer:

Notice: The Occupational Safety and Health Administration (OSHA) and the American Disabilities Act (ADA) have set enforceable standards for slip-fall protection on walking surfaces. The ADA standards are the more stringent and require a minimum coefficient of friction (CoF) on level walking surfaces of 0.6 and on ramped walking surfaces of 0.8. The system applicator/ end user assumes all responsibility to provide a flooring system that meets all current safety standards. Neither Durável nor its selling agents will be responsible for any injury that may be incurred in a slip-fall accident. Furthermore, Durável recommends the use of slip-resistant aggregate in all coatings or floor systems that could possibly be exposed to wet conditions or become contaminated with oils, grease, or other potential lubricants.

Storage:

Store in closed, properly labeled containers in a cool, ventilated area. Do not transfer contents to bottles or other unlabeled containers. Keep away from heat, open flames and oxidizing agents.

Disposal:

Wastes and contaminated packaging disposal should be in accordance with applicable regional, national and local laws and regulations.

Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature. May be extended with reasonable care.

Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet.

Warranty:

IMPORTANT!

Before using any Durável product, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY – VISIT Durável.com FOR THE LATEST VERSION.

Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

Safety Instructions:

For Professional Use Only

Keep Out of Reach of Children and Animals

May form combustible dust concentrations in the air. IF IN EYES: Immediately flush with copious amounts of water for at least 20 minutes. If eye irritation persists: Get medical advice/ attention. IF SWALLOWED: Immediately call a POISON CONTROL CENTER/ doctor. Do not induce vomiting. Aspiration hazard. Dilute with 1-2 glasses of water. Get medical aid. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. IF ON SKIN (or hair): Remove contaminated clothing. Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice or attention. IF INHALED: Unlikely during normal usage. Remove victim to fresh air and provide oxygen if breathing is difficult. Immediate medical attention not normally required. No delayed effects expected. Call a POISON CENTER/doctor if you feel unwell

.

Always Review SDS & Technical Data Prior to Use