Liquid Bonding Agent

Durável LBA is a ready-to-use liquid bonding agent designed to help cement-based materials bond to porous concrete surfaces. It is a thin primer used with several Durável systems and is available in 1-gallon jugs and 5-gallon pails.

Typical Uses:

- **Bonding Agent For Durável TRM**
- **Bonding Agent For Durável SOM**
- **Very Porous Surfaces Prior To Trowel Overlay**
- **Optional Primer For In-Fluence Stains**

Product Advantages :

- **Improves Bond Of Overlays To Concrete**
- **Simple Ready-To-Use Formula**
- **Slows Hydration, Increases Working Time**
- **Low Odor**

Ready to use

Application Temperature, Substrate
45° to 90° F

VOC Content
< 10 g/L

Packaging:
1-Gallon Jugs | 5-Gallon Pails

SURFACE PREPARATION

Technical Data

Coverage:

150 to 200 sq ft per gallon depending on the porosity of the profiled surface. Apply in a test area to determine actual coverage.

Directions for Use:

Substrate Preparation:

Follow the surface preparation instructions listed for the specific repair mortar, overlay, or topcoat being used.

Mixing Instructions:

Durável LBA is ready to use before applying concrete coatings to properly profiled concrete. Shake or stir well before application.

When using Durável LBA as a primer for In-Fluence stains, dilute 48 oz of Durável LBA with 80 oz of water.

Application Instructions:

Apply Durável LBA with a pump-up sprayer, paint roller, or brush in a thin, even coat. Do not allow the product to pond or puddle. Brush out or backroll any material that collects in joints, low spots, or uneven areas. Applying too much LBA, or leaving a heavy film on the surface, can cause bonding problems with the next coating or overlay.

FOR PROFESSIONAL USE ONLY

Wait for LBA to become tacky or dry before installing overlay materials. At 70°F and 50% humidity, overlay coatings may usually be installed after about 30 minutes, but no later than 24 hours after application. After 24 hours, LBA must be applied again as a new coat.

Do not apply Durável LBA if the surface is damp or frozen. Do not apply when the air or surface temperature is below 45°F (7°C) or above 90°F (32.2°C).

Clean Up:

Clean tools, sprayers, and mixing vessels with soap and water.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Protect product from freezing.

Disposal:

Recycle and/or dispose of contents and containers in accordance with local, regional, national, and international regulations.

Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature. May be extended with reasonable care.

Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range.

Warranty:

IMPORTANT!

Before using any Durável product, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY – VISIT Durável.com FOR THE LATEST VERSION.

Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based

on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

Safety Instructions:

For Professional Use Only

Keep Out of Reach of Children and Animals

IF IN EYES: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs. IF ON SKIN: (or hair) Wash contaminated skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical attention if irritation occurs. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing becomes difficult. IF SWALLOWED: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

Do not use a solid water stream as it may scatter and spread fire. The product itself does not burn

Always Review SDS & Technical Data Prior to Use