

Liquid Bonding Agent

Durável LBA™ is a specially formulated, ready-to-use Liquid Bonding Agent that is designed to bond cementitious materials to porous concrete surfaces. Durável LBA is a thin primer for several Durável systems and is available in 1-gallon jugs and 5-gallon pails.

Typical Uses:

- **Bonding Agent for Durável TRM™ Repair Mortar**
- **Bonding Agent for Durável SOM™ Stampable Overlay**
- **Use Prior to Application of Troweled Overlay on Extremely Porous Surfaces**

Product Advantages:

- **Improves Bond of Overlays to Concrete Substrates**
- **Simple Ready-to-Use Formulation**
- **Low Odor**

Ready To Use

Mixing:

- Shake or Stir Well

Application Temperature:

45° to 90° F (7° to 32° C)

VOC:

Less than 10 g/L

Packaging:

1 Gallon Jugs
5 Gallon Pails

Coverage:

150 – 200 sq ft per gallon depending on the porosity of the profiled surface. Apply a test area to determine actual coverage for the specific concrete surface.

Storage:

Keep tightly closed in a dry and cool place. Protect from frost. To maintain product quality, do not store in heat or direct sunlight. Agitate before use. Electrical installations / working materials must comply with the technological safety standards. Recommended storage temperature: 41-95°F / 5-35°C

Directions for Use:

Substrate Preparation:

Refer to substrate preparation instructions for the selected topping material.

CONCRETE OVERLAYS

Technical Data

FOR PROFESSIONAL USE ONLY

Technical Data Sheet

Mixing Instructions:

Shake or stir well prior to application. Durável LBA is ready to use when applying concrete coatings to profiled concrete.

When used as a primer for In-Fluence™ stains, add 48 oz of Durável LBA to 80 oz of water.

Application Instructions:

Shake or mix well prior to application. Spray, roll, or brush Durável LBA™ in a thin, uniform application. DO NOT allow product to pond or puddle during application or allow primer to form a heavy surface film. Avoid accumulating in joints and low spots by brushing out ponding or by backrolling. Overapplication can cause a bond failure for subsequent coatings.

Using a 3/8" – 1/2" roller, a long-handled brush, or a low-pressure sprayer, apply a thin even coat of primer to the surface. Allow Primer to get tacky or dry prior to application of concrete materials. Overlay coatings may be installed after approximately 30 minutes but no more than 24 hours after application (@ 70 F and 50 % humidity). Do not apply Durável LBA if the substrate is damp or frozen. Do not apply when the air or substrate temperature is below 45°F (7°C) or above 90°F (32.2°C).

Clean Up:

Clean tools and mixing vessels with water. Capture all concentrated product runoff as necessary to protect downstream surfaces.

Slip Resistance Disclaimer:

(Top Coat)

Disposal:

Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Shelf Life:

Generally one year from date of manufacture in original, unopened packaging stored at room temperature. Shelf life may be extended with reasonable care and protection during storage.

Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range.

Technical Data Sheet

Warranty:

IMPORTANT!

Before using all Durável products, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY - VISIT [Duravel.com](https://www.duravel.com) FOR THE LATEST VERSION

Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

Safety Instructions:

IF IN EYES: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

IF ON SKIN: (or hair) Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if irritation occurs.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing becomes difficult.

IF SWALLOWED: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

Always Review SDS & Technical Data Prior to Use

REV 01.30.2023