

Color Seal Pigment Pack

A-TINT is a high solids pigment pack formulated for use specifically with Durável Color Seal solvent acrylic sealer. Available in 14 standard colors. Use the recommended dose of pigment; excessive amounts of tint can cause pigment float and an uneven colored coating.

Typical Uses:

- Patios and Entrancesways
- Sidewalks
- Decks and Balconies
- Driveways
- Overlays

Product Advantages:

- Ultra Fine pigment for easy dispersion
- Field packs to reduce waste
- Economical for solid color applications
- UV Stable and chemically resistant.
- Low Odor

14 Standard Colors

Solid Opaque Coverage

UV Stable Pigment

Packaging:
32-ounce pigment packs

Coverage:

For a solid opaque finish add one 32-ounce container to one 5-gallon pail of Color Seal, or eight ounces per single gallon. A sample should be applied to make sure the proper color is achieved.

Directions for Use:

Mixing Instructions:

Always mix or mechanically shake A-Tint colorant prior to blending in the sealer. Add A-Tint to the sealer and slowly blend until solid color is achieved. Blend again during use as needed. Pigments will settle in stored products and may require emptying into a secondary container. Always box multiple containers together to achieve consistent color on a project.

FOR PROFESSIONAL USE ONLY

ACRYLIC PRODUCTS

Technical Data Sheet

Mixing Instructions:

Color Seal is a single component solvent acrylic sealer. The material should be stirred well prior to adding pigment application. Long-term storage may allow material to separate. Follow A-Tint instructions when adding pigment.

Clean Up:

Clean tools with Xylene

Storage:

Store in well-ventilated place. Keep Cool. Keep container tightly closed. Store locked up.

Disposal:

Disposal of product and packaging should be in accordance with applicable regional, national and local laws and regulations.

Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature.

Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range and to substrates that are a minimum of five degrees above dew point and will remain so during product cure. During application and cure protect product from all contaminants and traffic.

Warranty:

Durável® warrants our products to be of uniform quality, free from defects within manufacturing tolerances, and to conform to published specifications as of the date of sale. Durável® has no control over the use of the product and therefore no warranty, expressed or implied, is made or can be made as to the application of the product or the results of use. The manufacturer's obligations shall be limited to refunding the purchase price or providing replacement product for material proven to be defective. Ninety days after delivery of product all warranty and other duties with respect to the quality of the product delivered shall be presumed to have been conclusively satisfied, all liability therefore terminates, and no action for breach of any stated or implied duties may thereafter be commenced. The end user is responsible for determining the product's suitability and assumes all risks and liabilities. Under no circumstances will Durável® be subject to or held liable for a consequential damage to anyone in excess of the purchase price of the product.

Technical Data Sheet

Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável® assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the datasheet. Furthermore, Durável® assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

Technical Data Sheet

Safety Instructions:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/ lighting/ equipment. Use only non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

First Aid:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

If skin irritation occurs: Get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

IF SWALLOWED: Immediately call a POISON CONTROL CENTER/doctor

Do NOT induce vomiting.

Take off contaminated clothing and wash before reuse.

In case of fire use alcohol-resistant foam, dry chemical, halon, or carbon dioxide to extinguish. Collect spillage.



Always Review SDS & Technical Data Prior to Use

REV.05.18.2022