

## Solid Color Sealer for Decorative Concrete

Color Seal is a solid color solvent base acrylic concrete sealer for use on natural concrete and cement overlays. UV-stable A-Tint pigments are available in fourteen popular colors. The pigment is added as needed in the field to reduce waste.

### Typical Uses:

- Patios and Entrances
- Sidewalks
- Decks and Balconies
- Driveways
- Overlays

Solids Content – 25% by weight  
Dry Time, Tack Free – 1 to 2 hours  
Dry Time, Foot Traffic – 4 to 6 hours  
Dry Time, Heavy Traffic – 24 to 48 hours  
Recoat Interval – 4 to 24 hours

Application Temperature:  
Substrate - 50° to 80° F

VOC – less than < 700 g/L

Packaging:  
5-Gallon Pails

### Coverage:

Coverage rates will vary greatly depending on surface porosity and application method. Avoid a thick build of Color Seal. The product is designed to be used as thin coats and is not to be built up.

**First Coat:** varies with substrate porosity, typically 180 – 200 sq ft per gallon

**Second Coat:** 180 – 200 sq ft per gallon

### Directions for Use:

### Substrate Preparation:

**ENVIRONMENTAL CONDITIONS:** Rain should not be forecast for 24 hours after application. The product should be applied in thin coats. Applying Color Seal too thick may produce white spots that will need to be treated later. The product should be placed between 50° – 80° F surface temperature. If the product is applied outside of these temperature parameters the product may not cure properly and will not meet specifications in hardness or chemical resistance. The temperature should also be maintained during the curing process to avoid later issues.

**FOR PROFESSIONAL USE ONLY**

# Technical Data Sheet

## Mixing Instructions:

Color Seal is a single component solvent acrylic sealer. The material should be stirred well prior to adding pigment application. Long-term storage may allow material to separate. Follow A-Tint instructions when adding pigment.

## Application Instructions:

Color Seal is to be applied over dry substrates. Natural concrete must cure for at least 28 days. Cement overlays must be dry per their technical data sheet. Color Seal is applied by roller using a ½" or ¾" nap roller cover. Sealer should be applied in thin coats.

## Clean Up:

Xylene

## Maintenance:

Keep the surface free of sand and abrasives to minimize scratching. Use a pH-balanced cleaner with garden hose pressure water to remove light soils. Pressure washing sealer will reduce its service life. Spills should be cleaned promptly to prevent long-term staining.

## Cured Physical Properties:

Appearance, wet – Color  
Appearance, dry – Color, satin sheen  
Adhesion, Dry Concrete – Excellent  
Adhesion, Wet Concrete – Excellent  
Film Formation @ 40° F – Passed  
Mechanical Stability – Excellent  
Light Stability – Excellent  
Blush, 4 hr. dry @ 72° F, 18 hr. immersion – No Blush  
Hot Tire Pickup – Passed\*  
Water Resistance – Excellent, beads water  
Water Absorption – Passed

\* Under some circumstances, delaminating may occur. Not all tire manufacturers were not tested for Color Seal. Certain formulas/chemicals used in the tire manufacturing process could cause any sealers-coatings to fail from vehicular parking.

## Slip Resistance Disclaimer:

Notice: The Occupational Safety and Health Administration (OSHA) and the American Disabilities Act (ADA) have set enforceable standards for slip-fall protection on walking surfaces. The ADA standards are the more stringent and require a minimum coefficient of friction (CoF) on level walking surfaces of 0.6 and on ramped walking surfaces of 0.8. The system applicator/end-user assumes all responsibility to provide a flooring system

# Technical Data Sheet

that meets all current safety standards. Neither Durável® nor its selling agents will be responsible for any injury that may be incurred in a slip-fall accident. Furthermore, Durável® recommends the use of slip-resistant aggregate in all coatings or floor systems that could possibly be exposed to wet conditions or become contaminated with oils, grease or other lubricants. Refer to the technical data sheet on acrylic wax floor finishes that meet the requirements for ASTM D2047.

## Storage:

Keep the container tightly closed in a dry and well-ventilated place. Containers that are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat. Keep from freezing. Store products above 50 degrees F/10 degrees C and below 95 degrees F/35 degrees C.

## Disposal:

Disposal of product and packaging should be in accordance with applicable regional, national and local laws and regulations.

## Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature.

## Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range and to substrates that are a minimum of five degrees above dew point and will remain so during product cure. During application and cure protect product from all contaminants and traffic.

## Warranty:

Durável® warrants our products to be of uniform quality, free from defects within manufacturing tolerances, and to conform to published specifications as of the date of sale. Durável® has no control over the use of the product and therefore no warranty, expressed or implied, is made or can be made as to the application of the product or the results of use. The manufacturer's obligations shall be limited to refunding the purchase price or providing replacement product for material proven to be defective. Ninety days after delivery of product all warranty and other duties with respect to the quality of the product delivered shall be presumed to have been conclusively satisfied, all liability therefore terminates, and no action for breach of any stated or implied duties may thereafter be commenced. The end user is responsible for determining the product's suitability and assumes all risks and liabilities. Under no circumstances will Durável® be subject to or held liable for a consequential damage to anyone in excess of the purchase price of the product.

## Disclaimer:

# Technical Data Sheet

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável® assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável® assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

## Safety Instructions:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/ lighting/ equipment. Use only non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

### First Aid:

**IF ON SKIN** (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
If skin irritation occurs: Get medical advice or attention.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

**IF SWALLOWED:** Immediately call a POISON CONTROL CENTER/doctor

Do NOT induce vomiting.

Take off contaminated clothing and wash before reuse

In case of fire use alcohol-resistant foam, dry chemical, halon, or carbon dioxide to extinguish. Collect spillage.

**PROP65 WARNING:** This product contains chemicals known to the state of California to birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



**Always Review SDS & Technical Data Prior to Use**

REV.05.17.2022