

## Micronized Polymer Traction Additive

D-Grip micronized polymer traction additive provides increased slip-fall protection when added to a range of solvent base concrete floor coatings. There are three sizes: D-Grip (40 mesh), D-Grip Fine (100 mesh) and D-Grip HD (16 mesh). Unlike typical polypropylene products, the clear polymer of D-Grip does not significantly reduce the gloss or color of sealer. D-Grip mixes easily into solvent sealers and stays suspended with minimal additional stirring.

### Typical Uses:

- Swimming Pool Decks
- Driveways and Sidewalks
- Stamped Concrete
- Patios and Garages
- Other Interior and Exterior Surfaces

### Product Advantages:

- Mixes Easily and Stays Suspended
- Only Slight Loss of Gloss
- Range of Sizes

**D-Grip Fine:** Fine 100 mesh

**D-Grip:** Standard 40 mesh

**D-Grip HD:** Heavy Duty 16 mesh

### Directions for Use:

### Mixing Instructions:

Color Seal is a single component solvent acrylic sealer. The material should be stirred well prior to adding pigment application. Long-term storage may allow material to separate. Follow A-Tint instructions when adding pigment.

### Application Instructions:

Color Seal is to be applied over dry substrates. Natural concrete must cure for at least 28 days. Cement overlays must be dry per their technical datasheet. Color Seal is applied by roller using a 1/2" or 3/4" nap roller cover. Sealer should be applied in thin coats.

**FOR PROFESSIONAL USE ONLY**

**SLIP-FALL PROTECTION**

# Technical Data Sheet

## Slip Resistance Disclaimer:

Notice: The Occupational Safety and Health Administration (OSHA) and the American Disabilities Act (ADA) have set enforceable standards for slip-fall protection on walking surfaces. The ADA standards are the more stringent and require a minimum coefficient of friction (CoF) on level walking surfaces of 0.6 and on ramped walking surfaces of 0.8. The system applicator / end user assumes all responsibility to provide a flooring system that meets all current safety standards. Neither Durável nor its selling agents will be responsible for any injury that may be incurred in a slip-fall accident. Furthermore, Durável recommends the use of slip-resistant aggregate in all coatings or floor systems that could possibly be exposed to wet conditions or become contaminated with oils, grease or other lubricants. Refer to the technical data sheet on acrylic wax floor finishes that meet requirements for ASTM D2047.

## Storage:

Keep the container tightly closed in a dry and well-ventilated place. Containers that are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat. Keep from freezing. Store products above 50 degrees F/10 degrees C and below 95 degrees F/35 degrees C.

## Disposal:

Disposal of product and packaging should be in accordance with applicable regional, national and local laws and regulations.

## Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature.

## Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range and to substrates that are a minimum of five degrees above dew point and will remain so during product cure. During application and cure protect product from all contaminants and traffic.

## Warranty:

Durável® warrants our products to be of uniform quality, free from defects within manufacturing tolerances, and to conform to published specifications as of the date of sale. Durável® has no control over the use of the product and therefore no warranty, expressed or implied, is made or can be made as to the application of the product or the results of use. The manufacturer's obligations shall be limited to refunding the purchase price or providing replacement product for material proven to be defective. Ninety days after delivery of product all

# Technical Data Sheet

warranty and other duties with respect to the quality of the product delivered shall be presumed to have been conclusively satisfied, all liability therefore terminates, and no action for breach of any stated or implied duties may thereafter be commenced. The end user is responsible for determining the product's suitability and assumes all risks and liabilities. Under no circumstances will Durável® be subject to or held liable for a consequential damage to anyone in excess of the purchase price of the product.

## Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável® assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável® assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

## Safety Instructions:

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash face, hands, and any exposed skin thoroughly after handling. Wear protective gloves.

### First Aid:

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**IF SWALLOWED:** Immediately call a POISON CONTROL CENTER/doctor.

**IF ON SKIN:** (or hair): Wash with plenty of soap and water. If skin irritation occurs: Get medical advice or attention.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. If skin irritation occurs: Get medical advice or attention.



**Always Review SDS & Technical Data Prior to Use**

REV.05.18.2022